NEUMATI

A-U-D-I

SOUNDING OUT AUDIBLE DEVICES

Ancillaries - PAD PULSER

(C)

PAD PULSER

An output device for the most effective method of operating

PNEUMATIC AUDIBLE DEVICES

Creates adjustable, alternating pulses of pneumatic signals to give 'on-off' sounds

The **PAD PULSER** fits between the initial operating device and any PAD unit to convert a continuous signal to variable frequency of signals

Setting 1

Setting 2

Setting 3

See over for **Technical Specification** & check other 'Ancillaries' data sheets for details of operating devices and sensors **PAD PULSER**



PAD PULSER - 2020

A U D

SOUNDING OUT AUDIBLE DEVICES

(C)

Technical Specification


PAD PULSER




MODEL CODE PAD-PULSER-1 1/8" BSP & 4mm

OPERATION

Setting 1 Setting 2 Setting 3



DIMENSIONS




MATERIALS OF CONSTRUCTION

Brass - Internal parts Stainless Steel - Springs NBR - Seals

WEIGHT 275gms - without fittings

PRESSURE - maximum 10bar/148psi

PAD AIR CONSUMPTION



OPERATION BENEFITS

As well as using the **PAD PULSER** to identify different alarm levels changing from continuous sound to intermittent will reduce air flow EG Setting 1 x 25% Setting 2 x 40% Setting 3 x 60%

IMPORTANT DO NOT OPERATE ANY PAD UNITS CLOSE TO THE HUMAN EAR

All data quoted is approximate and provided for guidance purposes only

